Metamark 7 Series

High Performance Calendered Sign Vinyl



Product Description

Metamark 7 Series is a high performance calendered vinyl developed for computer-cut graphics for vehicles, window decals, and long term applications onto flat or slightly curved surfaces. The soft handle 70 micron face film offers ease of weeding, while the high grade solvent based adhesive allows wet application and clean removal. The product also benefits from a layflat PE liner. Exterior durability is 8 years for black and white, 7 years for colours and 5 years for metallic colours. M7-100C white gloss has a blue contrast liner.

Typical Applications

The range offers excellent cutting and weeding characteristics, and exterior durability of up to 8 years making it ideal for use on external applications including vehicle graphics and exterior sign applications.

Application Guidelines

- May be applied with a wet or dry application.
- Apply unstressed, in particular to curves and recesses. It is not suitable for application over rivets or complex recesses.
- Not recommended for use on low energy surfaces such as polypropylene. The user should determine suitability of all substrates refer to www.metamark.co.uk/ technical for advice on application surfaces.

Face Film		Printed	Metamark 7 Series in Purple print
с. сч.		Gauge	145 mym nominal
Face Film:	Polymeric calendered PVC	Weight	140 gsm nominal
Gauge:	70 micron nominal	Finishes	
Tensile Strength	47N/25mm MD / 43N/25mm TD 180% MD nominal	FIIIISIIES	
Elongation at break	-0.5% MD max / -0.2% TD max	Finishes Available	Ed aloos and 0 matt
Shrinkage	-0.5% MD Max / -0.2% TD Max	Finishes Available	54 gloss and 2 matt
Adhesive		Durability	
Туре	Permanent solvent-based acrylic	Shelf I ife	2 years
Weight	22gsm nominal	External weathering	8 years for black and white, 7 years for
Adhesion to glass 20 mins	15N/25mm nominal	External meathering	colours and 5 years for metallics; in
Adhesion to glass 24 hour	20N/25mm nominal		vertical exposure under northern
Perceived tack	Medium		European conditions.
Shear strength	Medium to high	Fire Rating	Class B. BS EN 13501-1:2007
Application temperature	+5°C to +60°C		BS 6853:1999 Cat1a&b (Passenger Rail)
Service temperature	-30°C to +110°C		EN ISO 5659-2 (Goods Rail Vehicles)
·			ISO 5658-2 (Goods Rail Vehicles)
Release Liner		Chemical Resistance	Resistant to mineral oils, fats and
-			fuels, aliphatic solvents, mild acids, salt
Туре	Advanced specially treated layflat		and alkali for e.g. diesel oil, gasoline,
	kraft paper with high internal strength		paraffin, hydraulic oil, antifreeze, soap
	and PE coating		suds etc.

Warranty: Metamark (UK) Limited warrants to its customers that completed decorative markings which utilise Metamark SignVinyl will remain in good condition without excessive fading or colour degradation for the specified life time of each material when correctly stored and applied in accordance with procedures outlined in the technical literature. If within the specified years of normal use Metamark SignVinyl becomes ineffective for its intended use, then Metamark will provide sufficient material to produce a new replacement marking, and will also, at its own discretion, contribute an allowance towards the costs involved in replacing the graphics. **Please Note:** The above data is given in good faith to provide an indication of the performance of the product. Purchasers should consider the suitability of each product for its intended use and the purchaser assumes all risks in connection with such use. Seller shall not be liable for damages in excess of the purchase price of the product nor for incidental nor consequential loss.

Metamark (UK) Limited

Octimum Business Park Forsyth Road Woking GU21 5SF Tel +44 (0)1483 571111 Fax +44 (0)1483 570540
Luneside New Quay Road Lancaster LA1 5QP Tel +44 (0)1524 387140 Fax + (0)1524 387147